

P-PIPE

P-PIPE Basic data sheet

P-PIPE Basic 1 Standard insert

Seal tightness
tested by independent
institute

The classic pipe seal.



P-PIPE Basic is ideal for use in the plumbing, heating and air-conditioning trades as well as in civil engineering and pipeline construction. P-PIPE Basic is the only press seal with an integrated torque control. This increases safety and shortens the duration of assembly.

P-PIPE Basic 1 is the perfect seal of pipes to be newly installed or which have already been laid in core drills or wall sleeves up to Ø 500 mm.

With 8 seal sizes and 3 seal widths, the most common pipe sizes from 32 mm up to 450 mm and the most important loading conditions can be sealed.



P-PIPE Basic 1

P-PIPE Basic – the advantages at a glance.

- absolutely gas and watertight
- sealing width 20 mm, up to 1 bar pressure-tight
- sealing width 40 and 80 mm, up to 2.5 bar pressure-tight
- stainless steel V2A (AISI 304L)
- for core drillings/wall sleeves up to 500 mm diameter
- pipe sizes 32 mm to 450 mm diameter
- easy to install
- integrated torque control
- U-profile: maximum stability with minimum material use

Hauff-Technik active principles – the intelligent difference.


Reliable and controlled.

Mechanical press seal systems for cable and pipe sealing. Closed, split, all shapes and sizes.



Visible and tangible.

Torque indication.



hauff
technik

Cable and Pipe Sealing Systems

• Through-the-wall intelligence.

Technical data for P-PIPE Basic 1. Standard insert

Core drilling/wall sleeve diameter IDs (mm)	Suitable for media pipe diameter ODs (mm)		Sealing width 20 mm (non-pressing water)	Sealing width 40 mm (pressing water)	Sealing width 80 mm (pressing water)
	from	to	Article design.	Article design.	Article design.
100	32	33,7	HSN 100/32	HSD 100/32	HSDD 100/32
100	40	42,4	HSN 100/40	HSD 100/40	HSDD 100/40
100	48	50	HSN 100/48	HSD 100/48	HSDD 100/48
100	60	63	HSN 100/60	HSD 100/60	HSDD 100/60
125	60	63	HSN 125/60	HSD 125/60	HSDD 125/60
125	75	76,1	HSN 125/75	HSD 125/75	HSDD 125/75
125	78	80	HSN 125/78	HSD 125/78	HSDD 125/78
150	78	80	HSN 150/78	HSD 150/78	HSDD 150/78
150	88	92	HSN 150/88	HSD 150/88	HSDD 150/88
150	110	112	HSN 150/110	HSD 150/110	HSDD 150/110
200	110	112	HSN 200/110	HSD 200/110	HSDD 200/110
200	114	118	HSN 200/114	HSD 200/114	HSDD 200/114
200	125	127	HSN 200/125	HSD 200/125	HSDD 200/125
200	133	135	HSN 200/133	HSD 200/133	HSDD 200/133
200	139	140	HSN 200/139	HSD 200/139	HSDD 200/139
200	159	162	HSN 200/159	HSD 200/159	HSDD 200/159
250	159	162	—	HSD-G 250/159	HSDD 250/159
250	168	170	—	HSD-G 250/168	HSDD 250/168
250	177	180	—	HSD-G 250/177	HSDD 250/177
250	200	200	—	HSD-G 250/200	HSDD 250/200
250	210	210	—	HSD-G 250/210	HSDD 250/210
300	200	200	—	HSD-G 300/200	HSDD 300/200
300	210	210	—	HSD-G 300/210	HSDD 300/210
300	219	219	—	HSD-G 300/219	HSDD 300/219
300	225	225	—	HSD-G 300/225	HSDD 300/225
300	250	250	—	HSD-G 300/250	HSDD 300/250
400	273	274	—	HSD-G 400/273	HSDD 400/273
400	277	280	—	HSD-G 400/277	HSDD 400/277
400	315	319	—	HSD-G 400/315	HSDD 400/315
400	324	326	—	HSD-G 400/324	HSDD 400/324
500	400	400	—	HSD-G 500/400	HSDD 500/400
500	429	429	—	HSD-G 500/429	HSDD 500/429
500	450	450	—	HSD-G 500/450	HSDD 500/450

For pipe sealings > Ø 250 mm our sealings are supplied in split version.



e.g. HSN200/159



e.g. HSD 200/159



e.g. HSDD200/159

We are there for you.

Whatever your requirements and wishes, we can supply any version to meet your needs. Fast and affordable. Contact us! We will be happy to advise you personally.