

# Korja-Kumi Oy



**KIILAHIIHNAT**

**TUULETTAJANHIHNAT**

**MONIURAHIIHNAT**

**KIILAHIIHNAT**

**TUULETTAJANHIHNAT**

**MONIURAHIIHNAT**

**KIILAHIIHNAT**

**TUULETTAJANHIHNAT**

**MONIURAHIIHNAT**

**HIHNAT 110**




## CLASSICAL SECTION : Z

Wrapped V-Belts

Standard : ISO 4183, ISO 4184, BS 3790, DIN 2215

Features :

- Oil resistant • Antistatic
- Temperature range : -18°C to +70°C
- Maximum belt linear speed : 30 m/sec
- ATEX certified FRAS belts are available



Z Section

Belt Length Factor (mm)			Manufacturing Range	Weight per metre (Kgs)
Lp to La	Li to Lp	Li to La		
16	22	38	254 - 4953 mm	0.057

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness (mm)		
Z	10	6	40	50 dp (mm)

Nominal Length (Inches) : Li

'PIX' FRAS belts conforms to: II 2GD c IIB X (Test report no. IB-03-4-934)

Z / 10x6

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

Tuote n:o	Hihnatyyppi / mitat	Profiili
1102000	KIILAHIHNA Z-15 / 10 x 381 mm Li	
1102001	KIILAHIHNA Z-16 / 10 x 410 mm Li	
1102002	KIILAHIHNA Z-17 / 10 x 435 mm Li	
1102003	KIILAHIHNA Z-18 / 10 x 457 mm Li	
1102004	KIILAHIHNA Z-19 / 10 x 480 mm Li	
1102005	KIILAHIHNA Z-20 / 10 x 510 mm Li	
1102006	KIILAHIHNA Z-21 / 10 x 535 mm Li	
1102007	KIILAHIHNA Z-22 / 10 x 560 mm Li	
1102008	KIILAHIHNA Z-23 / 10 x 585 mm Li	
1102009	KIILAHIHNA Z-24 / 10 x 610 mm Li	
1102010	KIILAHIHNA Z-25 / 10 x 635 mm Li	
1102011	KIILAHIHNA Z-26 / 10 x 660 mm Li	
1102013	KIILAHIHNA Z-28 / 10 x 710 mm Li	
1102016	KIILAHIHNA Z-31 / 10 x 790 mm Li	
1102017	KIILAHIHNA Z-32 / 10 x 815 mm Li	
1102018	KIILAHIHNA Z-33 / 10 x 840 mm Li	
1102019	KIILAHIHNA Z-34 / 10 x 865 mm Li	
1102020	KIILAHIHNA Z-35 / 10 x 890 mm Li	
1102021	KIILAHIHNA Z-36 / 10 x 914 mm Li	
1102023	KIILAHIHNA Z-38 / 10 x 965 mm Li	
1102027	KIILAHIHNA Z-42 / 10 x 1065 mm Li	
1102031	KIILAHIHNA Z-46 / 10 x 1168 mm Li	
1102033	KIILAHIHNA Z-48 / 10 x 1220 mm Li	
1102034	KIILAHIHNA Z-49 / 10 x 1250 mm Li	
1102035	KIILAHIHNA Z-50 / 10 x 1270 mm Li	
1102036	KIILAHIHNA Z-51 / 10 x 1300 mm Li	
1102040	KIILAHIHNA Z-55 / 10 x 1400 mm Li	
1102045	KIILAHIHNA Z-60 / 10 x 1525 mm Li	
1102049	KIILAHIHNA Z-64 / 10 x 1625 mm Li	
1102053	KIILAHIHNA Z-68 / 10 x 1725 mm Li	
1102056	KIILAHIHNA Z-71 / 10 x 1800 mm Li	
1102060	KIILAHIHNA Z-75 / 10 x 1900 mm Li	


## CLASSICAL SECTION : A

Wrapped V-Belts

Standard : ISO 4183, ISO 4184, BS 3790, DIN 2215

Features :

- Oil resistant • Antistatic
- Temperature range : -18°C to +70°C
- Maximum belt linear speed : 30 m/sec
- ATEX certified FRAS belts are available



Belt Length Factor (mm)			Manufacturing Range	Weight per metre (Kgs)
Lp to La	Li to Lp	Li to La		
14	36	50	330 - 9652 mm	0.106

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness (mm)		
A	13	8	40	75 dp (mm)

Nominal Length (inches) : Li

'PIX' FRAS belts conforms to: II 2GD c IIB X (Test report no. IB-03-4-934)

**A / 13x8**

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

## Tuote n:o Hihnatyyppi / mitat

## Profiili

1102098	KIILAHIHNA A-18 / 13 x 457 mm Li
1102099	KIILAHIHNA A-19 / 13 x 480 mm Li
1102100	KIILAHIHNA A-20 / 13 x 510 mm Li
1102101	KIILAHIHNA A-21 / 13 x 535 mm Li
1102102	KIILAHIHNA A-22 / 13 x 560 mm Li
1102103	KIILAHIHNA A-23 / 13 x 585 mm Li
1102104	KIILAHIHNA A-24 / 13 x 610 mm Li
1102105	KIILAHIHNA A-25 / 13 x 635 mm Li
1102106	KIILAHIHNA A-26 / 13 x 660 mm Li
1102106P	KIILAHIHNA A-26.5 / 13x 675 mm Li
1102107	KIILAHIHNA A-27 / 13 x 686 mm Li
1102108	KIILAHIHNA A-28 / 13 x 710 mm Li
1102109	KIILAHIHNA A-29 / 13 x 735 mm Li
1102110	KIILAHIHNA A-30 / 13 x 760 mm Li
1102111	KIILAHIHNA A-31 / 13 x 790 mm Li
1102111P	KIILAHIHNA A-31.5 / 13x 800 mm Li
1102112	KIILAHIHNA A-32 / 13 x 815 mm Li
1102113	KIILAHIHNA A-33 / 13 x 840 mm Li
1102114	KIILAHIHNA A-34 / 13 x 865 mm Li
1102115	KIILAHIHNA A-35 / 13 x 890 mm Li
1102116	KIILAHIHNA A-36 / 13 x 914 mm Li
1102117	KIILAHIHNA A-37 / 13 x 940 mm Li
1102118	KIILAHIHNA A-38 / 13 x 965 mm Li
1102119	KIILAHIHNA A-39 / 13 x 990 mm Li
1102120	KIILAHIHNA A-40 / 13 x 1016 mm Li
1102121	KIILAHIHNA A-41 / 13 x 1041 mm Li
1102122	KIILAHIHNA A-42 / 13 x 1065 mm Li
1102123	KIILAHIHNA A-43 / 13 x 1090 mm Li
1102124	KIILAHIHNA A-44 / 13 x 1120 mm Li
1102125	KIILAHIHNA A-45 / 13 x 1143 mm Li

Tuote n:o	Hihnatyyppi / mitat	Profiili
1102126	KIILAHIHNA A-46 / 13 x 1168 mm Li	
1102127	KIILAHIHNA A-47 / 13 x 1190 mm Li	
1102128	KIILAHIHNA A-48 / 13 x 1220 mm Li	
1102129	KIILAHIHNA A-49 / 13 x 1250 mm Li	
1102130	KIILAHIHNA A-50 / 13 x 1270 mm Li	
1102131	KIILAHIHNA A-51 / 13 x 1300 mm Li	
1102132	KIILAHIHNA A-52 / 13 x 1320 mm Li	
1102133	KIILAHIHNA A-53 / 13 x 1350 mm Li	
1102134	KIILAHIHNA A-54 / 13 x 1375 mm Li	
1102135	KIILAHIHNA A-55 / 13 x 1400 mm Li	
1102136	KIILAHIHNA A-56 / 13 x 1422 mm Li	
1102137	KIILAHIHNA A-57 / 13 x 1450 mm Li	
1102138	KIILAHIHNA A-58 / 13 x 1475 mm Li	
1102139	KIILAHIHNA A-59 / 13 x 1500 mm Li	
1102140	KIILAHIHNA A-60 / 13 x 1525 mm Li	
1102141	KIILAHIHNA A-61 / 13 x 1550 mm Li	
1102142	KIILAHIHNA A-62 / 13 x 1575 mm Li	
1102143	KIILAHIHNA A-63 / 13 x 1600 mm Li	
1102144	KIILAHIHNA A-64 / 13 x 1625 mm Li	
1102145	KIILAHIHNA A-65 / 13 x 1650 mm Li	
1102146	KIILAHIHNA A-66 / 13 x 1676 mm Li	
1102147	KIILAHIHNA A-67 / 13 x 1700 mm Li	
1102148	KIILAHIHNA A-68 / 13 x 1725 mm Li	
1102149	KIILAHIHNA A-69 / 13 x 1750 mm Li	
1102150	KIILAHIHNA A-70 / 13 x 1775 mm Li	
1102151	KIILAHIHNA A-71 / 13 x 1800 mm Li	
1102152	KIILAHIHNA A-72 / 13 x 1830 mm Li	
1102153	KIILAHIHNA A-73 / 13 x 1854 mm Li	
1102154	KIILAHIHNA A-74 / 13 x 1880 mm Li	
1102155	KIILAHIHNA A-75 / 13 x 1900 mm Li	
1102156	KIILAHIHNA A-76 / 13 x 1930 mm Li	
1102157	KIILAHIHNA A-77 / 13 x 1956 mm Li	
1102158	KIILAHIHNA A-78 / 13 x 1980 mm Li	
1102159	KIILAHIHNA A-79 / 13 x 2000 mm Li	
1102160	KIILAHIHNA A-80 / 13 x 2032 mm Li	
1102163	KIILAHIHNA A-83 / 13 x 2100 mm Li	
1102164	KIILAHIHNA A-84 / 13 x 2134 mm Li	
1102165	KIILAHIHNA A-85 / 13 x 2160 mm Li	

Tuote n:o	Hihnatyyppi / mitat	Profiili
1102167	KIILAHIHNA A-87 / 13 x 2210 mm Li	
1102168	KIILAHIHNA A-88 / 13 x 2240 mm Li	
1102170	KIILAHIHNA A-90 / 13 x 2286 mm Li	
1102171	KIILAHIHNA A-91 / 13 x 2311 mm Li	
1102174	KIILAHIHNA A-94 / 13 x 2388 mm Li	
1102176	KIILAHIHNA A-96 / 13 x 2438 mm Li	
1102177	KIILAHIHNA A-97 / 13 x 2464 mm Li	
1102180	KIILAHIHNA A-100 /13 x 2540 mm Li	
1102181	KIILAHIHNA A-104 /13 x 2650 mm Li	
1102182	KIILAHIHNA A-105 /13 x 2667 mm Li	
1102184	KIILAHIHNA A-112 /13 x 2845 mm Li	
1102186	KIILAHIHNA A-120 /13 x 3050 mm Li	
1102188	KIILAHIHNA A-128 /13 x 3250 mm Li	
1102189	KIILAHIHNA A-132 /13 x 3350 mm Li	
1102190	KIILAHIHNA A-136 /13 x 3450 mm Li	
1102192	KIILAHIHNA A-144 /13 x 3658 mm Li	
1102194	KIILAHIHNA A-158 /13 x 4000 mm Li	


## CLASSICAL SECTION : B

### Wrapped V-Belts

Standard : ISO 4183, ISO 4184, BS 3790, DIN 2215

#### Features :

- Oil resistant • Antistatic
- Temperature range : -18°C to +70°C
- Maximum belt linear speed : 30 m/sec
- ATEX certified FRAS belts are available



Belt Length Factor (mm)			Manufacturing Range	Weight per metre (Kgs)
Lp to La	Li to Lp	Li to La		
26	43	69	406 - 16713 mm	0.182

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thicknes s (mm)		
B	17	11	40	125 dp (mm)

Nominal Length (inches) : Li

'PIX' FRAS belts conforms to: II 2GD c IIB X (Test report no. IB-03-4-934)

**B / 17x11**

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

## Tuote n:o Hihnatyyppi / mitat

## Profiili

1102194B	KIILAHIHNA B-21 / 17 x 535 mm Li
1102195	KIILAHIHNA B-23 / 17 x 585 mm Li
1102196	KIILAHIHNA B-24 / 17 x 610 mm Li
1102197	KIILAHIHNA B-25 / 17 x 635 mm Li
1102198	KIILAHIHNA B-26 / 17 x 660 mm Li
1102199	KIILAHIHNA B-27 / 17 x 686 mm Li
1102200	KIILAHIHNA B-28 / 17 x 710 mm Li
1102201	KIILAHIHNA B-29 / 17 x 735 mm Li
1102202	KIILAHIHNA B-30 / 17 x 760 mm Li
1102203	KIILAHIHNA B-31 / 17 x 790 mm Li
1102204	KIILAHIHNA B-32 / 17 x 815 mm Li
1102205	KIILAHIHNA B-33 / 17 x 840 mm Li
1102206	KIILAHIHNA B-34 / 17 x 865 mm Li
1102207	KIILAHIHNA B-35 / 17 x 890 mm Li
1102208	KIILAHIHNA B-36 / 17 x 914 mm Li
1102209	KIILAHIHNA B-37 / 17 x 940 mm Li
1102210	KIILAHIHNA B-38 / 17 x 965 mm Li
1102211	KIILAHIHNA B-39 / 17 x 990 mm Li
1102212	KIILAHIHNA B-40 / 17 x 1016 mm Li
1102213	KIILAHIHNA B-41 / 17 x 1041 mm Li
1102214	KIILAHIHNA B-42 / 17 x 1065 mm Li
1102215	KIILAHIHNA B-43 / 17 x 1090 mm Li
1102216	KIILAHIHNA B-44 / 17 x 1120 mm Li
1102217	KIILAHIHNA B-45 / 17 x 1143 mm Li
1102218	KIILAHIHNA B-46 / 17 x 1168 mm Li
1102219	KIILAHIHNA B-47 / 17 x 1190 mm Li
1102220	KIILAHIHNA B-48 / 17 x 1220 mm Li

Tuote n:o	Hihnatyyppi / mitat	Profiili
1102221	KIILAHIHNA B-49 / 17 x 1250 mm Li	
1102222	KIILAHIHNA B-50 / 17 x 1270 mm Li	
1102223	KIILAHIHNA B-51 / 17 x 1300 mm Li	
1102224	KIILAHIHNA B-52 / 17 x 1320 mm Li	
1102225	KIILAHIHNA B-53 / 17 x 1350 mm Li	
1102227	KIILAHIHNA B-54 / 17 x 1375 mm Li	
1102228	KIILAHIHNA B-55 / 17 x 1400 mm Li	
1102229	KIILAHIHNA B-56 / 17 x 1422 mm Li	
1102230	KIILAHIHNA B-57 / 17 x 1450 mm Li	
1102231	KIILAHIHNA B-58 / 17 x 1475 mm Li	
1102232	KIILAHIHNA B-59 / 17 x 1500 mm Li	
1102233	KIILAHIHNA B-60 / 17 x 1525 mm Li	
1102234	KIILAHIHNA B-61 / 17 x 1550 mm Li	
1102235	KIILAHIHNA B-62 / 17 x 1575 mm Li	
1102236	KIILAHIHNA B-63 / 17 x 1600 mm Li	
1102237	KIILAHIHNA B-64 / 17 x 1625 mm Li	
1102238	KIILAHIHNA B-65 / 17 x 1650 mm Li	
1102239	KIILAHIHNA B-66 / 17 x 1676 mm Li	
1102240	KIILAHIHNA B-67 / 17 x 1700 mm Li	
1102241	KIILAHIHNA B-68 / 17 x 1725 mm Li	
1102242	KIILAHIHNA B-69 / 17 x 1750 mm Li	
1102243	KIILAHIHNA B-70 / 17 x 1775 mm Li	
1102244	KIILAHIHNA B-71 / 17 x 1800 mm Li	
1102245	KIILAHIHNA B-72 / 17 x 1830 mm Li	
1102246	KIILAHIHNA B-73 / 17 x 1854 mm Li	
1102247	KIILAHIHNA B-74 / 17 x 1880 mm Li	
1102248	KIILAHIHNA B-75 / 17 x 1900 mm Li	
1102249	KIILAHIHNA B-76 / 17 x 1930 mm Li	
1102251	KIILAHIHNA B-78 / 17 x 1980 mm Li	
1102253	KIILAHIHNA B-80 / 17 x 2032 mm Li	
1102254	KIILAHIHNA B-81 / 17 x 2060 mm Li	
1102257	KIILAHIHNA B-84 / 17 x 2134 mm Li	
1102258	KIILAHIHNA B-85 / 17 x 2160 mm Li	
1102259	KIILAHIHNA B-86 / 17 x 2184 mm Li	



Tuote n:o	Hihnatyyppi / mitat	Profiili
1102263	KIILAHIHNA B-90 / 17 x 2286 mm Li	
1102267	KIILAHIHNA B-94 / 17 x 2388 mm Li	
1102270	KIILAHIHNA B-97 / 17 x 2464 mm Li	
1102271	KIILAHIHNA B-105 /17 x 2667 mm Li	
1102272	KIILAHIHNA B-110 /17 x 2800 mm Li	
1102273	KIILAHIHNA B-112 /17 x 2845 mm Li	
1102274	KIILAHIHNA B-116 /17 x 2950 mm Li	
1102275	KIILAHIHNA B-118 /17 x 3000 mm Li	
1102276	KIILAHIHNA B-120 /17 x 3050 mm Li	
1102277	KIILAHIHNA B-122 /17 x 3100 mm Li	
1102277B	KIILAHIHNA B-124 / 17 x 3150 mm Li	
1102278	KIILAHIHNA B-128 /17 x 3250 mm Li	
1102279	KIILAHIHNA B-136 /17 x 3450 mm Li	
1102280	KIILAHIHNA B-144 /17 x 3658 mm Li	
1102281	KIILAHIHNA B-152 /17 x 3860 mm Li	
1102282	KIILAHIHNA B-158 /17 x 4000 mm Li	
1102283	KIILAHIHNA B-162 /17 x 4115 mm Li	
1102284	KIILAHIHNA B-173 /17 x 4394 mm Li	
1102285	KIILAHIHNA B-180 /17 x 4572 mm Li	
1102286	KIILAHIHNA B-186 /17 x 4724 mm Li	
1102287	KIILAHIHNA B-195 /17 x 4950 mm Li	
1102288	KIILAHIHNA B-210 /17 x 5330 mm Li	
1102289	KIILAHIHNA B-225 /17 x 5715 mm Li	
1102290	KIILAHIHNA B-240 /17 x 6100 mm Li	
1102291	KIILAHIHNA B-264 /17 x 6700 mm Li	


## CLASSICAL SECTION : C

### Wrapped V-Belts

Standard : ISO 4183, ISO 4184, BS 3790, DIN 2215

#### Features :

- Oil resistant • Antistatic
- Temperature range : -18°C to +70°C
- Maximum belt linear speed : 30 m/sec
- ATEX certified FRAS belts are available



C Section

Belt Length Factor (mm)			Manufacturing Range	Weight per metre (Kgs)
Lp to La	Li to Lp	Li to La		
32	56	88	788 - 16713 mm	0.298

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness (mm)		
C	22	14	40	200 dp (mm)

Nominal Length (inches) : Li

'PIX' FRAS belts conforms to : II 2GD c IIB X (Test report no. IB-03-4-934)

**C / 22x14**

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

## Tuote n:o Hihnatyyppi / mitat

## Profiili

1102301	KIILAHIHNA C-51 / 22 x 1300 mm Li
1102303	KIILAHIHNA C-60 / 22 x 1525 mm Li
1102305	KIILAHIHNA C-68 / 22 x 1725 mm Li
1102307	KIILAHIHNA C-71 / 22 x 1800 mm Li
1102309	KIILAHIHNA C-75 / 22 x 1900 mm Li
1102311	KIILAHIHNA C-80 / 22 x 2032 mm Li
1102313	KIILAHIHNA C-85 / 22 x 2160 mm Li
1102315	KIILAHIHNA C-90 / 22 x 2286 mm Li
1102317	KIILAHIHNA C-97 / 22 x 2464 mm Li
1102319	KIILAHIHNA C-105 / 22 x 2667 mm Li
1102321	KIILAHIHNA C-112 / 22 x 2845 mm Li
1102323	KIILAHIHNA C-120 / 22 x 3050 mm Li
1102325	KIILAHIHNA C-128 / 22 x 3250 mm Li
1102327	KIILAHIHNA C-136 / 22 x 3450 mm Li
1102329	KIILAHIHNA C-144 / 22 x 3658 mm Li
1102333	KIILAHIHNA C-158 / 22 x 4000 mm Li
1102335	KIILAHIHNA C-162 / 22 x 4115 mm Li
1102337	KIILAHIHNA C-173 / 22 x 4394 mm Li
1102339	KIILAHIHNA C-180 / 22 x 4572 mm Li
1102341	KIILAHIHNA C-195 / 22 x 4950 mm Li
1102343	KIILAHIHNA C-210 / 22 x 5330 mm Li
1102347	KIILAHIHNA C-240 / 22 x 6100 mm Li
1102349	KIILAHIHNA C-270 / 22 x 6858 mm Li


### WEDGE SECTION : SPZ

Wrapped V-B elts

Standard : BS 3790/DIN 7753

#### Features :

- Oil resistant
- Antistatic
- Temperature range : -18°C to +70°C
- Maximum belt linear speed : 42 m/sec
- ATEX certified FRAS belts are available



Belt Length Factor (mm)			Manufacturing Range	Weight per metre (Kgs)
Lp to La	Li to Lp	Li to La	365 - 4953 mm	0.070
13	37	50		

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness (mm)		
SPZ	10	8	40	67 dp (mm)

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

Tuote n:o	Hihnatyyppi / mitat	Profiili
1102401	KIILAHIHNA SPZ-630 / 9,5 x 593 mm Li	(3V250)
1102403	KIILAHIHNA SPZ-670 / 9,5 x 633 mm Li	(3V265)
1102405	KIILAHIHNA SPZ-710 / 9,5 x 673 mm Li	(3V280)
1102407	KIILAHIHNA SPZ-760 / 9,5 x 723 mm Li	(3V300)
1102409	KIILAHIHNA SPZ-800 / 9,5 x 763 mm Li	(3V315)
1102411	KIILAHIHNA SPZ-850 / 9,5 x 813 mm Li	(3V335)
1102413	KIILAHIHNA SPZ-900 / 9,5 x 863 mm Li	(3V355)
1102415	KIILAHIHNA SPZ-950 / 9,5 x 913 mm Li	(3V375)
1102417	KIILAHIHNA SPZ-1000 / 9,5 x 963 mm Li	
1102419	KIILAHIHNA SPZ-1037 / 9,5 x 1000 mm Li	
1102420	KIILAHIHNA SPZ-1060 / 9,5 x 1023 mm Li	
1102423	KIILAHIHNA SPZ-1120 / 9,5 x 1080 mm Li	
1102426	KIILAHIHNA SPZ-1137 / 9,5 x 1100 mm Li	(3V450)
1102429	KIILAHIHNA SPZ-1180 / 9,5 x 1143 mm Li	
1102432	KIILAHIHNA SPZ-1200 / 9,5 x 1163 mm Li	(3V475)
1102433	KIILAHIHNA SPZ-1212 / 9,5 x 1175 mm Li	
1102434	KIILAHIHNA SPZ-1237 / 9,5 x 1200 mm Li	
1102435	KIILAHIHNA SPZ-1250 / 9,5 x 1213 mm Li	
1102438	KIILAHIHNA SPZ-1262 / 9,5 x 1225 mm Li	(3V500)
1102441	KIILAHIHNA SPZ-1320 / 9,5 x 1283 mm Li	
1102442	KIILAHIHNA SPZ-1337 / 9,5 x 1300 mm Li	
1102444	KIILAHIHNA SPZ-1400 / 9,5 x 1363 mm Li	
1102447	KIILAHIHNA SPZ-1412 / 9,5 x 1375 mm Li	(3V560)
1102450	KIILAHIHNA SPZ-1500 / 9,5 x 1463 mm Li	
1102453	KIILAHIHNA SPZ-1600 / 9,5 x 1563 mm Li	(3V630)
1102456	KIILAHIHNA SPZ-1700 / 9,5 x 1663 mm Li	(3V670)

Tuote n:o	Hihnatyyppi / mitat	Profiili
1102459	KIILAHIHNA SPZ-1800 / 9,5 x 1763 mm Li	(3V710)
1102462	KIILAHIHNA SPZ-1900 / 9,5 x 1863 mm Li	(3V750)
1102465	KIILAHIHNA SPZ-2000 / 9,5 x 1963 mm Li	
1102468	KIILAHIHNA SPZ-2037 / 9,5 x 2000 mm Li	(3V800)
1102471	KIILAHIHNA SPZ-2120 / 9,5 x 2083 mm Li	
1102474	KIILAHIHNA SPZ-2150 / 9,5 x 2123 mm Li	(3V850)
1102477	KIILAHIHNA SPZ-2240 / 9,5 x 2203 mm Li	
1102480	KIILAHIHNA SPZ-2287 / 9,5 x 2243 mm Li	(3V900)
1102483	KIILAHIHNA SPZ-2360 / 9,5 x 2323 mm Li	
1102485	KIILAHIHNA SPZ-2410 / 9,5 x 2373 mm Li	(3V950)
1102486	KIILAHIHNA SPZ-2500 / 9,5 x 2463 mm Li	
1102487	KIILAHIHNA SPZ-2540 / 9,5 x 2503 mm Li	(3V1000)
1102488	KIILAHIHNA SPZ-2650 / 9,5 x 2613 mm Li	
1102489	KIILAHIHNA SPZ-2690 / 9,5 x 2653 mm Li	(3V1060)
1102490	KIILAHIHNA SPZ-2800 / 9,5 x 2763 mm Li	
1102491	KIILAHIHNA SPZ-2840 / 9,5 x 2803 mm Li	(3V1120)
1102492	KIILAHIHNA SPZ-3000 / 9,5 x 2963 mm Li	(3V1180)
1102493	KIILAHIHNA SPZ-3150 / 9,5 x 3113 mm Li	(3V1250)
1102494	KIILAHIHNA SPZ-3350 / 9,5 x 3313 mm Li	(3V1320)
1102495	KIILAHIHNA SPZ-3550 / 9,5 x 3513 mm Li	(3V1400)


WEDGE SECTION : SPA

Wrapped V-Belts

Standard : BS 3790/DIN 7753

Features :

- Oil resistant
- Antistatic
- Temperature range : -18°C to +70°C
- Maximum belt linear speed : 42 m/sec
- ATEX certified FRAS belts are available



Belt Length Factor (mm)			Manufacturing Range	Weight per metre (Kgs)
Lp to La	Li to Lp	Li to La		
18	45	63	576 - 9246 mm	0.119

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness (mm)		
SPA	13	10	40	100 dp (mm)

Nominal Length : Pitch length Lp in mm  
 'PIX' FRAS belts conforms to: II 2GD c IIB X (Test report no. IB-03-4-934)

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

## Tuote n:o Hihnatyyppi / mitat

## Profiili

1102501	KIILAHIHNA SPA-800 / 12,5 x 755 mm Li
1102503	KIILAHIHNA SPA-850 / 12,5 x 805 mm Li
1102505	KIILAHIHNA SPA-900 / 12,5 x 855 mm Li
1102507	KIILAHIHNA SPA-950 / 12,5 x 905 mm Li
1102509	KIILAHIHNA SPA-1000 / 12,5 x 955 mm Li
1102511	KIILAHIHNA SPA-1060 / 12,5 x 1015 mm Li
1102513	KIILAHIHNA SPA-1120 / 12,5 x 1075 mm Li
1102514	KIILAHIHNA SPA-1132 / 12,5 x 1087 mm Li
1102514P	KIILAHIHNA SPA-1157 / 12,5 x 1112 mm Li
1102515	KIILAHIHNA SPA-1180 / 12,5 x 1135 mm Li
1102517	KIILAHIHNA SPA-1250 / 12,5 x 1205 mm Li
1102519	KIILAHIHNA SPA-1320 / 12,5 x 1275 mm Li
1102521	KIILAHIHNA SPA-1400 / 12,5 x 1355 mm Li
1102523	KIILAHIHNA SPA-1500 / 12,5 x 1455 mm Li
1102525	KIILAHIHNA SPA-1600 / 12,5 x 1555 mm Li
1102527	KIILAHIHNA SPA-1700 / 12,5 x 1655 mm Li
1102529	KIILAHIHNA SPA-1800 / 12,5 x 1755 mm Li
1102531	KIILAHIHNA SPA-1900 / 12,5 x 1855 mm Li
1102533	KIILAHIHNA SPA-2000 / 12,5 x 1955 mm Li
1102535	KIILAHIHNA SPA-2120 / 12,5 x 2075 mm Li
1102537	KIILAHIHNA SPA-2240 / 12,5 x 2195 mm Li
1102539	KIILAHIHNA SPA-2360 / 12,5 x 2315 mm Li
1102561	KIILAHIHNA SPA-2500 / 12,5 x 2455 mm Li
1102564	KIILAHIHNA SPA-2650 / 12,5 x 2605 mm Li
1102566	KIILAHIHNA SPA-2800 / 12,5 x 2755 mm Li


WEDGE SECTION : SPB

Wrapped V-Belts

Standard : BS 3790/DIN 7753

Features :

- Oil resistant
- Antistatic
- Temperature range : -18°C to +70°C
- Maximum belt linear speed : 42 m/sec
- ATEX certified FRAS belts are available



Belt Length Factor (mm)			Manufacturing Range	Weight per metre (Kgs)
Lp to La	Li to Lp	Li to La		
28	60	88	940 - 16764 mm	0.214

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness (mm)		
SPB	17	14	40	160 dp (mm)

Nominal Length : Pitch length Lp in mm  
 'PIX' FRAS belts conforms to: II 2GD c IIB X (Test report no. IB-03-4-934)

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

Tuote n:o	Hihnatyyppi / mitat	Profiili
1102601	KIILAHIHNA SPB-1250 / 16 x 1190 mm Li	
1102603	KIILAHIHNA SPB-1320 / 16 x 1260 mm Li	
1102605	KIILAHIHNA SPB-1400 / 16 x 1340 mm Li	
1102607	KIILAHIHNA SPB-1500 / 16 x 1440 mm Li	
1102609	KIILAHIHNA SPB-1600 / 16 x 1540 mm Li	
1102611	KIILAHIHNA SPB-1700 / 16 x 1640 mm Li	
1102613	KIILAHIHNA SPB-1800 / 16 x 1740 mm Li	
1102615	KIILAHIHNA SPB-1900 / 16 x 1840 mm Li	(5V750)
1102617	KIILAHIHNA SPB-2000 / 16 x 1940 mm Li	
1102619	KIILAHIHNA SPB-2020 / 16 x 1960 mm Li	(5V800)
1102621	KIILAHIHNA SPB-2120 / 16 x 2060 mm Li	
1102623	KIILAHIHNA SPB-2150 / 16 x 2090 mm Li	(5V850)
1102625	KIILAHIHNA SPB-2240 / 16 x 2180 mm Li	
1102627	KIILAHIHNA SPB-2280 / 16 x 2220 mm Li	(5V-900)
1102629	KIILAHIHNA SPB-2360 / 16 x 2300 mm Li	
1102629X	KIILAHIHNA SPB-2360 XHR	
1102631	KIILAHIHNA SPB-2400 / 16 x 2340 mm Li	(5V 950)
1102633	KIILAHIHNA SPB-2500 / 16 x 2440 mm Li	
1102635	KIILAHIHNA SPB-2530 / 16 x 2470 mm Li	
1102637	KIILAHIHNA SPB-2650 / 16 x 2590 mm Li	
1102639	KIILAHIHNA SPB-2680 / 16 x 2620 mm Li	(5V 1060)
1102641	KIILAHIHNA SPB-2800 / 16 x 2740 mm Li	
1102643	KIILAHIHNA SPB-2840 / 16 x 2780 mm Li	(5V1120)
1102645	KIILAHIHNA SPB-3000 / 16 x 2940 mm Li	
1102647	KIILAHIHNA SPB-3150 / 16 x 3090 mm Li	
1102649	KIILAHIHNA SPB-3350 / 16 x 3290 mm Li	(5V1320)
1102651	KIILAHIHNA SPB-3550 / 16 x 3490 mm Li	(5V1400)

Tuote n:o Hihnatyyppi / mitat

Profiili

**JATKETTAVA KIILAHIHNA**

1102880	JATKETTAVA KIILAHIHNA PROF. Z, 10/6 mm
1102881	JATKETTAVA KIILAHIHNA PROF. A, 13/8 mm
1102882	JATKETTAVA KIILAHIHNA PROF. B, 17/11 mm
1102883	JATKETTAVA KIILAHIHNA PROF. C, 22/14 mm


**JATKETTAVAN KIILAHIHNAN LIITIN**

1102885	JATK.KIILAHIHNAN LIITIN PROF. Z
1102886	JATK.KIILAHIHNAN LIITIN PROF. A
1102887	JATK.KIILAHIHNAN LIITIN PROF. B
1102888	JATK.KIILAHIHNAN LIITIN PROF. C

AUTOMOTIVE BELTS : AVX10  
Raw Edge Cogged Belts  
Standard : DIN 7753

Features :

- Maximum power transmission • Antistatic
- Moulded cogs for extra flexibility
- Resistant to Oil & Heat
- Good abrasion resistance
- Low stretch
- Smooth on high speed engines
- High power transmission on small pulley diameters



Manufacturing Range	Weight per metre (Kgs)
600 - 5130 mm (La)	0.0713



Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness(mm)		
AVX10	9.5	8	36	56 mm (dp)

Nominal Length = Outside Length in MM (La)

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

## Tuote n:o Hihnatyyppi / mitat

## Profiili

H0950510	TUULET.HIHNA 9.5 x 510La (460 Li)
H0950600	TUULET.HIHNA 9.5 x 600La (550 Li)
H0950615	TUULET.HIHNA 9.5 x 615La (565 Li)
H0950625	TUULET.HIHNA 9.5 x 625La (575 Li)
H0950650	TUULET.HIHNA 9.5 x 650La (600 Li)
H0950675	TUULET.HIHNA 9.5 x 675La (625 Li)
H0950690	TUULET.HIHNA 9.5 x 690La (640 Li)
H0950700	TUULET.HIHNA 9.5 x 700La (650 Li)
H0950725	TUULET.HIHNA 9.5 x 725La (675 Li)
H0950740	TUULET.HIHNA 9.5 x 735 La (685 Li)
H0950750	TUULET.HIHNA 9.5 x 750La (700 Li)
H0950765	TUULET.HIHNA 9.5 x 765La (715 Li)
H0950775	TUULET.HIHNA 9.5 x 775La (725 Li)
H0950790	TUULET.HIHNA 9.5 x 790La (740 Li)
H0950800	TUULET.HIHNA 9.5 x 800La (750 Li)
H0950825	TUULET.HIHNA 9.5 x 825La (775 Li)
H0950835	TUULET.HIHNA 9.5 x 835La (785 Li)
H0950850	TUULET.HIHNA 9.5 x 850La (800 Li)
H0950865	TUULET.HIHNA 9.5 x 865La (815 Li)
H0950875	TUULET.HIHNA 9.5 x 875 La (825 Li)
H0950890	TUULET.HIHNA 9.5 x 890La (840 Li)
H0950900	TUULET.HIHNA 9.5 x 900La (850 Li)
H0950915	TUULET.HIHNA 9.5 x 915La (865 Li)
H0950925	TUULET.HIHNA 9.5 x 925La (875 Li)



Tuote n:o	Hihnatyyppi / mitat	Profiili
H0950940	TUULET.HIHNA 9.5 x 940La (890 Li)	
H0950950	TUULET.HIHNA 9.5 x 950La (900 Li)	
H0950965	TUULET.HIHNA 9.5 x 965La (915 Li)	
H0950975	TUULET.HIHNA 9.5 x 975La (925 Li)	
H0950990	TUULET.HIHNA 9.5 x 990La (940 Li)	
H0951000	TUULET.HIHNA 9.5 x 1000La (950 Li)	
H0951025	TUULET.HIHNA 9.5 x 1025La (975 Li)	
H0951050	TUULET.HIHNA 9.5 x 1050La (1000 Li)	
H0951075	TUULET.HIHNA 9.5 x 1075La (1025 Li)	
H0951090	TUULET.HIHNA 9.5 x 1090La (1040 Li)	
H0951105	TUULET.HIHNA 9.5 x 1100La (1050 Li)	
H0951125	TUULET.HIHNA 9.5 x 1125La (1075 Li)	
H0951150	TUULET.HIHNA 9.5 x 1150La (1100 Li)	
H0951175	TUULET.HIHNA 9.5 x 1175La (1125 Li)	
H0951200	TUULET.HIHNA 9.5 x 1200La (1150 Li)	
H0951225	TUULET.HIHNA 9.5 x 1225La (1175 Li)	
H0951250	TUULET.HIHNA 9.5 x 1250La (1200 Li)	
H0951275	TUULET.HIHNA 9.5 x 1275La (1225 Li)	
H0951300	TUULET.HIHNA 9.5 x 1300La (1250 Li)	
H0951325	TUULET.HIHNA 9.5 x 1325La (1275 Li)	
H0951350	TUULET.HIHNA 9.5 x 1350La (1300 Li)	
H0951375	TUULET.HIHNA 9.5 x 1375La (1325 Li)	
H0951400	TUULET.HIHNA 9.5 x 1400La (1350 Li)	
H0951425	TUULET.HIHNA 9.5 x 1425La (1375 Li)	
H0951450	TUULET.HIHNA 9.5 x 1450La (1400 Li)	
H0951475	TUULET.HIHNA 9.5 x 1475La (1425 Li)	
H0951500	TUULET.HIHNA 9.5 x 1500La (1450 Li)	
H0951550	TUULET.HIHNA 9.5 x 1550La (1500 Li)	
H0951575	TUULET.HIHNA 9.5 x 1575La (1525 Li)	
H0951600	TUULET.HIHNA 9.5 x 1600La (1550 Li)	
H0951625	TUULET.HIHNA 9.5 x 1625La (1575 Li)	
H0951650	TUULET.HIHNA 9.5 x 1650La (1600 Li)	
H0951675	TUULET.HIHNA 9.5 x 1675La (1625 Li)	


## AUTOMOTIVE BELTS : AVX11

Raw Edge Cogged Belts

Standard : DIN 7753

### Features :

- Maximum power transmission • Antistatic
- Moulded cogs for extra flexibility
- Resistant to Oil & Heat
- Good abrasion resistance
- Low stretch
- Smooth on high speed engines
- High power transmission on small pulley diameters



Manufacturing Range	Weight per metre (Kgs)
381 - 4928 mm (La)	0.0881

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness(mm)		
AVX11	10.5	8	36	64 mm (de)

Nominal Length (inches) = Belt No./10 = La



Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

### Tuote n:o Hihnatyyppi / mitat

### Profiili

H1190665	TUULET.HIHNA 11.9 x 665La (610 Li)
H1190765	TUULET.HIHNA 11.9 x 765La (710 Li)
H1190775	TUULET.HIHNA 11.9 x 775La (720 Li)
H1190790	TUULET.HIHNA 11.9 x 790La (735 Li)
H1190800	TUULET.HIHNA 11.9 x 800La (745 Li)
H1190865	TUULET.HIHNA 11.9 x 865La (810 Li)
H1190875	TUULET.HIHNA 11.9 x 875La (820 Li)
H1190890	TUULET.HIHNA 11.9 x 890La (835 Li)
H1190925	TUULET.HIHNA 11.9 x 925La (870 Li)
H1190950	TUULET.HIHNA 11.9 x 950La (895 Li)
H1191000	TUULET.HIHNA 11.9 x 1000La (945 Li)
H1191035	TUULET.HIHNA 11.9 x 1035La (980 Li)
H1191050	TUULET.HIHNA 11.9 x 1050La (995 Li)
H1191150	TUULET.HIHNA 11.9 x 1150La (1095 Li)
H1191175	TUULET.HIHNA 11.9 x 1175La (1120 Li)
H1191180	TUULET.HIHNA 11.9 x 1180La (1125 Li)
H1191215	TUULET.HIHNA 11.9 x 1215La (1160 Li)


## AUTOMOTIVE BELTS : AVX13

Raw Edge Cogged Belts

Standard : DIN 7753

### Features :

- Maximum power transmission • Antistatic
- Moulded cogs for extra flexibility
- Resistant to Oil & Heat
- Good abrasion resistance
- Low stretch
- Smooth on high speed engines
- High power transmission on small pulley diameters



Manufacturing Range	Weight per metre (Kgs)
600 - 5143 mm (La)	0.122

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness(mm)		
AVX13	12.5	10	36	71 mm (dp)

Nominal Length = Outside Length in MM (La)



Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

## Tuote n:o Hihnatyyppi / mitat

## Profiili

H1250600	TUULET.HIHNA 12.5 x 600La (540 Li)
H1250660	TUULET.HIHNA 12.5 x 660La (600 Li)
H1250685	TUULET.HIHNA 12.5 x 685La (625 Li)
H1250700	TUULET.HIHNA 12.5 x 700La (640 Li)
H1250725	TUULET.HIHNA 12.5 x 725La (665 Li)
H1250750	TUULET.HIHNA 12.5 x 750La (690 Li)
H1250775	TUULET.HIHNA 12.5 x 775La (715 Li)
H1250800	TUULET.HIHNA 12.5 x 800La (740 Li)
H1250825	TUULET.HIHNA 12.5 x 825La (765 Li)
H1250850	TUULET.HIHNA 12.5 x 850La (790 Li)
H1250875	TUULET.HIHNA 12.5 x 875La (815 Li)
H1250900	TUULET.HIHNA 12.5 x 900La (840 Li)
H1250915	TUULET.HIHNA 12.5 x 915La (855 Li)
H1250925	TUULET.HIHNA 12.5 x 925La (865 Li)
H1250950	TUULET.HIHNA 12.5 x 950La (890 Li)
H1250965	TUULET.HIHNA 12.5 x 965La (905 Li)
H1250975	TUULET.HIHNA 12.5 x 975La (915 Li)
H1250985	TUULET.HIHNA 12.5 x 990 La (930 Li)
H1251000	TUULET.HIHNA 12.5 x 1000La (940 Li)
H1251025	TUULET.HIHNA 12.5 x 1025La (965 Li)
H1251055	TUULET.HIHNA 12.5 x 1050La (990 Li)
H1251075	TUULET.HIHNA 12.5 x 1075La (1015 Li)
H1251100	TUULET.HIHNA 12.5 x 1100La (1040 Li)
H1251125	TUULET.HIHNA 12.5 x 1125 La (1065 Li)
H1251150	TUULET.HIHNA 12.5 x 1150La (1090 Li)

Tuote n:o	Hihnatyyppi / mitat	Profiili
H1251175	TUULET.HIHNA 12.5 x 1175La (1115 Li)	
H1251200	TUULET.HIHNA 12.5 x 1200La (1140 Li)	
H1251225	TUULET.HIHNA 12.5 x 1225La (1165 Li)	
H1251250	TUULET.HIHNA 12.5 x 1250La (1190 Li)	
H1251275	TUULET.HIHNA 12.5 x 1275La (1215 Li)	
H1251300	TUULET.HIHNA 12.5 x 1300La (1240 Li)	
H1251325	TUULET.HIHNA 12.5 x 1325 La (1265 Li)	
H1251350	TUULET.HIHNA 12.5 x 1350La (1290 Li)	
H1251375	TUULET.HIHNA 12.5 x 1375La (1315 Li)	
H1251400	TUULET.HIHNA 12.5 x 1400La (1340 Li)	
H1251425	TUULET.HIHNA 12.5 x 1425La (1365 Li)	
H1251450	TUULET.HIHNA 12.5 x 1450La (1390 Li)	
H1251475	TUULET.HIHNA 12.5 x 1475La (1415 Li)	
H1251500	TUULET.HIHNA 12.5 x 1500La (1440 Li)	
H1251525	TUULET.HIHNA 12.5 x 1525La (1465 Li)	
H1251550	TUULET.HIHNA 12.5 x 1550La (1490 Li)	
H1251575	TUULET.HIHNA 12.5 x 1575La (1515 Li)	
H1251600	TUULET.HIHNA 12.5 x 1600La (1540 Li)	
H1251610	TUULET.HIHNA 12.5 x 1610La (1550 Li)	
H1251625	TUULET.HIHNA 12.5 x 1625La (1565 Li)	
H1251650	TUULET.HIHNA 12.5 x 1650La (1590 Li)	
H1251675	TUULET.HIHNA 12.5 x 1675La (1615 Li)	
H1251700	TUULET.HIHNA 12.5 x 1700La (1640 Li)	
H1251800	TUULET.HIHNA 12.5 x 1800La (1740 Li)	
H1251825	TUULET.HIHNA 12.5 x 1825La (1765 Li)	
H1251900	TUULET.HIHNA 12.5 x 1900La (1840 Li)	
H1252030	TUULET.HIHNA 12.5 x 2030La (1970 Li)	
H1252350	TUULET.HIHNA 12.5 x 2350La (2290 Li)	


**AUTOMOTIVE BELTS : AVX17**

Raw Edge Cogged Belts

Standard : DIN 7753

**Features :**

- Maximum power transmission • Antistatic
- Moulded cogs for extra flexibility
- Resistant to Oil & Heat
- Good abrasion resistance
- Low stretch
- Smooth on high speed engines
- High power transmission on small pulley diameters



Manufacturing Range	Weight per metre (Kgs)
381 - 5149 mm (La)	0.178

Section	Dimensions		Angle Degree	Rec. Min Pulley Dia.
	Topwidth(mm)	Thickness(mm)		
AVX17	17	11.5	36	64 mm (de)

Nominal Length = Outside Length in MM (La)



Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

**Tuote n:o Hihnatyppi / mitat**

**Profiili**

H1700815	TUUL. HIHNA 17 x 815 Li(885 La)
H1701015	TUUL. HIHNA 17 x 1015 Li(1085 La)
H1701120	TUUL. HIHNA 17 x 1120 Li(1190 La)
H1701140	TUUL. HIHNA 17 x 1140 Li(1210 La)
H1701170	TUUL. HIHNA 17 x 1170 Li(1240 La)

**TUULETTAJAHIHNNAN MITTA**

H2000005 TUUL. HIHNAMITTA

**TUULETTAJAHIHNNAN TELINE**

H2000010 TUUL. HIHNATELINE 9.5-12.5/3-4PK  
H2000011 TUUL. HIHNATELINE 5-6PK


## AUTOMOTIVE BELTS : 3PK

Ribbed/Poly V-belt

Standard : RMA IP 26

### Features :

- High tensile strength • Antistatic
- Better flexibility
- less vibrations absorb shocks
- Low stretch
- Excellent behaviour under tension
- Capable to work on small pulley diameters
- Good wear resistance & quiet running



Manufacturing Range	Weight per metre/Rib (Kgs)
280 - 5080 mm	0.0153

Section	Dimensions		Max. Belt Speed m/sec	Rec. Min Pulley Dia.	Minimum Order Qty. (No. of Sleeves)
	Rib Pitch (mm)	Thickness (mm)			
PK	3.56	4.5	55	50 de (mm)	01

Nominal Length : Effective length Le

'PIX' FRAS belts conforms to: II 2GD c IIB X (Test report no. IB-03-4-934)

Merkkien selitys: Li = sisäpituus- La = ulkopituus - Lw (Ld/Lp) = laskentapituus

## Tuote n:o Hihnatyyppi / mitat

## Profiili

H3PK0735 MONIURAHIHNA 3PK x 735  
 H3PK0760 MONIURAHIHNA 3PK x 760  
 H3PK0765 MONIURAHIHNA 3PK x 765  
 H3PK0780 MONIURAHIHNA 3PK x 780  
 H3PK0805 MONIURAHIHNA 3PK x 805  
 H3PK0880 MONIURAHIHNA 3PK x 880  
 H3PK0910 MONIURAHIHNA 3PK x 910  
 H3PK0960 MONIURAHIHNA 3PK x 960  
 H3PK0975 MONIURAHIHNA 3PK x 975

H4PK0700 MONIURAHIHNA 4PK x 700  
 H4PK0755 MONIURAHIHNA 4PK x 755  
 H4PK0805 MONIURAHIHNA 4PK x 805  
 H4PK0815 MONIURAHIHNA 4PK x 815  
 H4PK0830 MONIURAHIHNA 4PK x 830  
 H4PK0840 MONIURAHIHNA 4PK x 840  
 H4PK0845 MONIURAHIHNA 4PK x 845  
 H4PK0865 MONIURAHIHNA 4PK x 865  
 H4PK0885 MONIURAHIHNA 4PK x 885  
 H4PK0935 MONIURAHIHNA 4PK x 0935  
 H4PK0950 MONIURAHIHNA 4PK x 950  
 H4PK0955 MONIURAHIHNA 4PK x 955  
 H4PK0960 MONIURAHIHNA 4PK x 960  
 H4PK0975 MONIURAHIHNA 4PK x 975  
 H4PK0985 MONIURAHIHNA 4PK x 985  
 H4PK0995 MONIURAHIHNA 4PK x 995

Tuote n:o	Hihnatyyppi / mitat	Profiili
H4PK1015	MONIURAHIHNA 4PK x 1015	
H4PK1520	MONIURAHIHNA 4PK x 1520	
H5PK0830	MONIURAHIHNA 5PK x 830	
H5PK0835	MONIURAHIHNA 5PK x 835	
H5PK0855	MONIURAHIHNA 5PK x 855	
H5PK0875	MONIURAHIHNA 5PK x 875	
H5PK0925	MONIURAHIHNA 5PK x 925	
H5PK0970	MONIURAHIHNA 5PK x 970	
H5PK0975	MONIURAHIHNA 5PK x 975	
H5PK1000	MONIURAHIHNA 5PK x 1000	
H5PK1010	MONIURAHIHNA 5PK x 1010	
H5PK1125	MONIURAHIHNA 5PK x 1125	
H5PK1165	MONIURAHIHNA 5PK x 1165	
H5PK1610	MONIURAHIHNA 5PK x 1610	
H6PK0735	MONIURAHIHNA 6PK x 735	
H6PK0885	MONIURAHIHNA 6PK x 885	
H6PK1015	MONIURAHIHNA 6PK x 1015	
H6PK1020	MONIURAHIHNA 6PK x 1020	
H6PK1080	MONIURAHIHNA 6PK x 1080	
H6PK1150	MONIURAHIHNA 6PK x 1150	
H6PK1180	MONIURAHIHNA 6PK x 1180	
H6PK1190	MONIURAHIHNA 6PK x 1190	
H6PK1885	MONIURAHIHNA 6PK x 1885	
H6PK1980	MONIURAHIHNA 6PK x 1980	
H6PK2030	MONIURAHIHNA 6PK x 2030	
H6PK2050	MONIURAHIHNA 6PK x 2050	
H6PK2120	MONIURAHIHNA 6PK x 2120	
H6PK2145	MONIURAHIHNA 6PK x 2145 La	
H8PK1425	MONIURAHIHNA 8PK x 1425 La	

