



## MANNOL TS-14 UHPD 7114

Innovative all-weather ester-containing synthetic motor oil for heavy-duty and high-speed diesel engines with and without turbocharger, operating in difficult conditions. The oil has successfully passed road and laboratory tests at VOLVO, MACK and RENAULT centres and has their written approvals.

Product properties:

- Ester components in combination with the highest quality synthetic base, featuring optimal viscosity in a wide temperature range, provide excellent anti-friction, anti-wear and anti-scuffing properties, which significantly extend the life of equipment in all, even the most extreme, operating modes in a wide range of ambient temperatures and provides significant fuel savings;
- The ester components in combination with a synthetic base provide increased thermal oxidative stability to the oil, which, in combination with excellent detergent-dispersant properties and low ash content, effectively reduces scaling and varnish formation, prevents deposits of all kinds and maintains engine parts in perfectly clean condition throughout the entire interval between replacements;
- A unique ester-containing formulation provides increased oil resistance to aging, and due to the reduced evaporation and high flash point, it reduces oil scaling "waste", which enables it to be used in engines with a long like interval and conventional motors;
- Due to the synthetic ester-containing base, the optimal viscosity has excellent low-temperature properties, including a low pour point, along with good oil pumpability and crankability of engine components at low temperatures, easy "cold start" (up to  $-30^{\circ}\text{C}$ ) and reduced startup wear;
- Compatible with all exhaust gas after-treatment systems: - DPF, TWC, EGR and SCR thanks to the use of Low SAPS technology;
- Effectively protects engine parts from all types of corrosion;
- Lower foam formation;
- Effectively deals with the increase in shear stress during operation caused by elevated viscosity due to soot dispersion;

Suitable for engines using fuelled by natural gas (LNG) and petroleum (LPG) gas.

Designed for all types of heavy duty diesel motors (long distance trucks, buses, etc.), off-road machinery (construction, mining, agricultural) and special equipment from European, American and Asian manufacturers that meet the requirements of Euro I – V where a performance level of CG-4 or lower is required.

Can be used in gasoline engines where API SN or lower performance is required.

SAE 15W-40  
API CJ-4/SN  
ACEA E7  
ACEA E9  
JASO DH-2  
CATERPILLAR ECF-3  
CUMMINS CES 20081  
DETROIT DIESEL 93K218  
DEUTZ DQC III-10 LA  
MACK EO-O Premium Plus  
MAN 3575  
MB 228.31  
RENAULT RLD-3  
SCANIA Low Ash  
VOLVO VDS-4

## PACKAGING

|       |            |         |            |
|-------|------------|---------|------------|
| 20L   | MN7114-20  | Plastic |            |
| 1000L | MN7114-IBC |         |            |
| 208L  | MN7114-DR  | Drum    |            |
| 60L   | MN7114-60  | Drum    |            |
| 7L    | MN7114-7   |         |            |
| 5L    | MN7114-5   |         |            |
| 1L    | MN7114-1   | Plastic | 20 pcs/box |