

Hydraulic mulchers

Robust construction

The TREJON OPTIMAL hydraulic mulching head is offered in two sizes and two models. It is well adapted to the mulching of vegetation on uneven ground under difficult conditions. The mulcher is very sturdy and its hydraulic motor can work continuously under high pressure with high efficiency.

All exposed parts of the mulcher head are made of HARDOX® steel, for extreme resistance to wear and a long service life. The side plates of the head are bent, which strengthens the structure and directs the cut material towards the ground, rather than keeping it inside the head.

Pivoting attachment, H-model

The H models are recommended for use while the machine is moving forward, such as along roads, where the pivoting attachment is practical. The H model heads are open at the front and have a chain curtain at the back, which increases safety when working along public roads.

Rigid attachment, HF-model

The hydraulic chain mulchers with rigid head attachment (the HF models) are recommended for use on uneven ground, such as in power lanes, where you want to clear a large area in front of the machine while standing still, and then move ahead, stepwise. These heads are open in two directions.



When mulching brushwood on uneven or inaccessible ground, the TREJON OPTIMAL hydraulic chain mulchers are the optimal choice. The head with pivoting attachment is fitted to a hydraulic machine, such as an excavator, for mulching vegetation along roads, power lanes, etc. The picture shows a model H mulcher.



TREJON OPTIMAL M160H3P with arm for 3-point connection.



Model H with pivoting attachment plate. Parts of the cutting head are in HARDOX® steel and the sides have double chassis. The machine can be fitted with extra wear skids for extra long life and maximum wear.

TECHNICAL DATA

Art.no/Model	M125H	M160H	M125HF	M160HF	M160H3P
Working width	1 250 mm	1 600 mm	1 250 mm	1 600 mm	1 600 mm
Width	1 500 mm	1 862 mm	1 500 mm	1 862 mm	1 862 mm
Height incl. by motor	807 mm	807 mm	807 mm	807 mm	807 mm
Wear parts	HARDOX® 500	HARDOX® 500	HARDOX® 500	HARDOX® 500	HARDOX® 500
Hardened chain	10 and 13 mm	10 and 13 mm	10 and 13 mm	10 and 13 mm	10 and 13 mm
Weight (incl. attachment)	340 kg	390 kg	340 kg	390 kg	500 kg
Operation, hydraulic	Axial piston motor	Axial piston motor	Axial piston motor	Axial piston motor	Axial piston motor
Min. req. oil flow	120 l/min	150 l/min	120 l/min	150 l/min	150 l/min
Min. oil pressure	180 bar	180 bar	180 bar	180 bar	180 bar
Attachment plate	Jointed	Jointed	Fixed	Fixed	Fixed
Price	7 495 €	8 795 €	7 495 €	8 795 €	9 995 €

The machine is delivered without attachment and hydraulic hoses.
Contact Trejon for correct attachment to your machine - specify pressure/flow with order.

ACCESSORIES

320157	Head attachment, Gate 540 (fits chain clearers of models H and HF)	240 €
320158	Head attachment, Gate 545 (fits chain clearers of models H and HF)	240 €
320159	Head attachment, Gate 550 (fits chain clearers of models H and HF)	250 €
345052	Wear skid in HARDOX® incl. bolt and nut. Fits all chain mulchers M125/M160. Machine requires 4 skids.	145 €