

TUUBI



Oil Pattern Distance **Forward Oil Total Tank Configuration**

40 11.24 mL N/A

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

10.28 mL **CURRENT**

30

Oil Per Board **Volume Oil Total Tank B Conditioner**

40 ul 21.52 mL **CURVE**

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	3L	3R	1	10	3	Α	35	0.0	0.0	0.0	1400
2	4L	5R	2	14	3	Α	64	0.0	3.9	3.9	2560
3	7L	7R	3	14	3	Α	81	3.9	9.8	5.9	3240
4	8L	8R	2	14	3	Α	50	9.8	13.7	3.9	2000
5	11L	11R	2	18	3	Α	38	13.7	18.8	5.1	1520
6	14L	14R	1	18	3	Α	13	18.8	21.3	2.5	520
7	3L	3R	0	18	3	Α	0	21.3	40.0	18.7	0
			_		_		_				_

1 2		2R	0				CROSSED	START	END	FEET	T.OIL
2	141		•	30	3	В	0	40.0	30.0	-10.0	0
	176	14R	1	18	3	В	13	30.0	27.5	-2.5	520
3	11L	11R	1	18	3	В	19	27.5	25.0	-2.5	760
4	10L	10R	2	18	3	В	42	25.0	19.9	-5.1	1680
5 9	9L	9R	2	18	3	В	46	19.9	14.8	-5.1	1840
6	8L	8R	2	14	3	В	50	14.8	10.9	-3.9	2000
7	7L	7R	2	14	3	В	54	10.9	7.0	-3.9	2160
8 4	4L	4R	1	10	3	В	33	7.0	5.6	-1.4	1320
9 :	3L	3R	0	10	3	В	0	5.6	0.0	-5.6	0

Cleaner Ratio Main Mix Forward 24:1 Cleaner Ratio Back End Mix 24:1 Reverse Cleaner Ratio Back End Distance 59 Combined

Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100







