

KIERREHIRMUJEN SYYSKAADOT 2023



Oil Pattern Distance Forward Oil Total Tank Configuration 46 12.96 mL N/A Reverse Brush Drop Reverse Oil Total Tank A Conditioner 40 7.16 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner

40 ul 20.12 mL CURRENT

1 3 2 8 3 3 4 9 5 4	8L 3L	3R 8R 3R	2 1 1	14 14			70 25	0.0	1.9	1.9	2800
3 3 4 9	3L	3R	_	14	4	Α	25	4.0			
4 9			1			•••	23	1.9	3.8	1.9	1000
	9L			14	4	Α	35	3.8	5.7	1.9	1400
5 4		9R	1	14	4	Α	23	5.7	7.6	1.9	920
	4L	4R	1	14	4	Α	33	7.6	9.5	1.9	1320
6 1	10L	10R	3	18	4	Α	63	9.5	17.1	7.6	2520
7 1	11L	11R	1	18	3	Α	19	17.1	19.6	2.5	760
8 1	12L	12R	1	18	3	Α	17	19.6	22.1	2.5	680
9 1	13L	13R	1	18	3	Α	15	22.1	24.6	2.5	600
10 1	14L	14R	1	18	3	Α	13	24.6	27.1	2.5	520
11 1	15L	15R	1	18	3	Α	11	27.1	29.6	2.5	440
12 2	2L	2R	0	10	3	Α	0	29.6	46.0	16.4	0

START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
2L	2R	0	30	1	В	0	46.0	37.0	-9.0	0
15L	15R	2	26	2	В	22	37.0	29.7	-7.3	880
14L	14R	1	26	2	В	13	29.7	26.1	-3.6	520
13L	13R	2	22	3	В	30	26.1	19.9	-6.2	1200
12L	12R	2	22	3	В	34	19.9	13.7	-6.2	1360
11L	11R	2	22	3	В	38	13.7	7.5	-6.2	1520
10L	10R	2	18	3	В	42	7.5	2.4	-5.1	1680
2L	2R	0	14	3	В	0	2.4	0.0	-2.4	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 24:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

ltem	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle: Inside Middle: Middle	
Track Zone Ratio	6.58	2.36	1.07	1.07	2.36	6.58



